

SAFETY DATA SHEET

Mx-19

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name Caine mix III 10.0% pet

Article Number Mx-19

Applications Diagnosis of contact allergy.

Manufacturer Chemotechnique Diagnostics AB

Modemgatan 9 SE-235 39 Vellinge

Telephone +46 (0) 40 466 077 (Monday-Friday 8.00-16.00)

Fax +46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	90.0%	-
Benzocaine	94-09-7	5.0%	-
Dibucaine	61-12-1	2.5%	Acute tox. Oral 4, Serious eye dam.
hydrochloride			1; H302, H318
Tetracaine	136-47-0	2.5%	Acute tox. Oral 3, Eye irrit. 2, Skin
hydrochloride			sensit. 1; H301, H317, H319

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8		-
Benzocaine	94-09-7	5.0%	-
Dibucaine hydrochloride	61-12-1	2.5%	Xn; R22, R41
Tetracaine hydrochloride	136-47-0	2.5%	T; R25, R36, R43

For the full text of the H-statements and R-phrases mentioned in this Section, see Section 16.

Mx-19 Version 2 Revision Date: 2013-06-27 Print Date: 2013-06-27 Page 1 of 4



4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents

Water with full jet.

Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to sunlight. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance White Semi-solid

Odour Odourless

Melting point* 50-55°C

Boiling point* No data available

Flash point* >100°C

Mx-19 Version 2 Revision Date: 2013-06-27 Print Date: 2013-06-27 Page 2 of 4



Self ignition* Product does not self ignite.

Danger of explosion* Product does not present an explosion hazard.

Density* No data available.

Solubility in/Miscibility with Water* Insoluble

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous byproducts

Combustion may generate CO, CO₂ and other oxides.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Oral 4 Acute toxicity, Oral (Category 3,4)

Eye irrit. 2 Eye irritation (Category 2)

Serious eye dam. 1 Serious eye damage (Category 1)
Skin sensit. 1 Skin sensitization (Category 1)

H301 Toxic if swallowed
H302 Harmful if swallowed

H317 May cause an allergic skin reaction

Mx-19 Version 2 Revision Date: 2013-06-27 Print Date: 2013-06-27 Page 3 of 4

^{*}Data is shown for petrolatum only



H318 Causes serious eye damage H319 Causes serious eye irritation

T Toxic
Xn Harmful

R22 Harmful if swallowed R25 Toxic if swallowed R36 Irritating to eyes

R41 Risk of serious damage to eyes.

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.

Mx-19 Version 2 Revision Date: 2013-06-27 Print Date: 2013-06-27 Page 4 of 4