

## SAFETY DATA SHEET

# O-010

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	ETHYLHEXYL TRIAZONE 10.0% pet
Article Number	O-010
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique Diagnostics AB Modemgatan 9 SE-235 39 Vellinge
Telephone	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00)
Fax	+46 (0) 40 466 700

## 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

## Signs and symptom of exposure

Dermal irritation.

# Medical conditions aggravated by exposure Dermatitis.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Conte nt	Classification
Petrolatum	8009-03-8	90.0%	-
ETHYLHEXYL TRIAZONE	88122-99-0	10.0%	Chron. aq. tox. 1; H413

Classification according to EU Directive 67/548/EEC and 1999/45/EC					
Component	CAS-No.	Content	Classification		
Petrolatum	8009-03-8		-		
ETHYLHEXYL TRIAZONE	88122-99-0	10.0%	N; R53		

For the full text of the H-statements and R-phrases mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

**Emergency and first aid procedures** Obtain medical attention.



#### 5. FIRE-FIGHTING MEASURES\*

#### Suitable extinguish media

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. **For safety reasons unsuitable extinguishing agents** Water with full jet.

**Special protective equipment for fire-fighters** Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

## 6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage** Store dark at 5-8°C. Avoid extended exposure to sunlight. FOR EXTERNAL USE ONLY.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Respiratory protection** Not required.

Ventilation Local exhaust.

Protective gloves Disposal gloves.

**Eye protection** Not required with normal use.

#### Work/Hygienic practices

Wash hands after each use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour Ivory White Semi-solid Odourless

Melting point\*50-55°CBoiling point\*No data availableFlash point\*>100°CSelf ignition\*Product does not self ignite.Danger of explosion\*Product does not present an explosion hazard.Density\*No data available.Solubility in/Miscibility with Water\*Insoluble

\*Data is shown for petrolatum only



## **10. STABILITY AND REACTIVITY**

#### Incompability

May react with strong oxidizing agents.

#### Stability

Stable at recommended storage conditions.

#### Hazardous byproducts

Combustion may generate CO, CO<sub>2</sub> and other oxides.

# Hazardous polymerization

Will not occur.

## **11. TOXICOLOGICAL INFORMATION**

No data available.

## 12. ECOLOGICAL INFORMATION

No data available.

## **13. DISPOSAL CONSIDERATIONS**

#### Waste disposal method

Comply with federal, state/provincial and local regulation.

#### **14. TRANSPORT INFORMATION**

Not dangerous goods.

## 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

#### **16. OTHER INFORMATION**

#### Text of H-statements and R-phrases mentioned in Section 3

Chron. aq. tox. 1	Chronic aquatic toxicity (Category 1)
H413	May cause long lasting harmful effects to aquatic life.
N	Dangerous for the environment
R53	May cause long term adverse effects in the aquatic
	environment.

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.